

# ORNATE FLUSH PIPE FITTING INSTRUCTIONS

## ASSEMBLY (LOW LEVEL)

- 1 Mount the cistern securely on the wall at the required height using the fixing holes through the rear of the cistern (N.B. the cistern lid must be situated a minimum of 1 metre from the floor to obtain a satisfactory flush.) See handy hint.
- 2 Place the ornate shroud and retaining ring (thinner of the two supplied) over the top of the flush pipe and insert into the threaded syphon stem (supplied as part of the cistern fittings). Once this is secure push the ornate shroud up to cover the fittings and secure with the retaining O ring.
- 3 Insert the lower end of the pipe into the pan via the multi-quick fitting (supplied as part of the cistern fittings).
- 4 Pass the cistern lever through the orifice on the cistern via the threaded sheath and secure with the locking nut. Slide the plastic washer over the cistern lever from inside the cistern, then hold all components in place by inserting the retaining pin through the pre-punched hole in the lever and bend to prevent it from moving. Lastly, slide the plastic fulcrum onto the lever, tighten the grub screw and join it to the existing 'S Hook' on the top of the syphon. (N.B. When installed the external ceramic handle of the lever should point towards 2 o'clock.)

## HANDY HINT

If you are installing your cistern on an outside wall, ensure that the black rubber spacing washers are used to create a small gap between the cistern back and the wall. There are two reasons for this; firstly it will help to reduce the possibility of condensation when cold mains pressure is contained within a humid environment. Secondly, the gap will help prevent 'thermal shock'. This is when rapid temperature change occurs (usually overnight) and causes the wall to contract or expand, thus cracking the sanitaryware. When fixing the cistern to the wall it is advisable to insert the screw through a washer (not supplied) on the inside of the cistern. This will prevent the screw damaging the sanitaryware when the screw 'bites'.

