




**Geberit Duofix frame for wall-hung WC, H112, with Sigma cistern 12 cm**


Geberit  
Sigma 12 cm (UP320)  
WS10009-20110209  
www.well-online.eu


**Application purpose**

- For installation of a wall-hung WC with bolt fixings set at 180 or 230 mm centres
- For installation in a room-height Duofix system wall in front of a solid or drywall construction
- For mounting in front of a solid or drywall construction
- For a screed of 0-200 mm (not in room height applications)
- For connecting Geberit AquaClean
- Any boarding must be fixed tight up against the face of the Duofix frame and screwed directly to the frame.

**Characteristics**

- Self-supporting
- Frame with C profile 40/40 mm
- Powder-coated frame, ultramarine blue
- Galvanised leg supports, steplessly adjustable 0-200 mm
- Feet can be retracted 50 mm
- Rotating foot plate, for installation in UW50 profiles
- Frame with holes  $\varnothing$  9 mm for fastening in wood frame construction
- Sound-absorbing actuator rods, tool-free, fast adjustment
- Concealed cistern for tool-free mounting and maintenance
- Frame height 1120 mm
- With wall anchors to allow up to a 200 mm duct. For larger ducts up to 400 mm use extension bolts 111.887.00.1
- Tool-free fastening for outlet bend, sound-absorbing, adjustable in depth with 8 positions, adjustable range 45 mm
- Connection hose to angle stop valve can be screwed without tools
- Water supply connection at centre back or at the top
- Geberit Sigma concealed cistern 12 cm with front actuation
- Dual flush with Sigma80 touchless, Sigma60, Sigma50, Sigma20, Sigma10 touchless, Sigma01 or Bolero flush plates
- Single flush with Sigma10 or Tango flush plates
- Dual flush with pneumatic buttons
- Single flush with touchless flush or pneumatic buttons
- The protection cover protects the service opening against moisture and dirt and can be mounted without tools and cut to length
- Universal water supply connection compatible with MeplaFix, can be mounted and operated without tools
- Self-locking feet for tool-free alignment of the frame, (friction feet have to be locked with spanner)
- For pans with contact surfaces smaller than 170 mm (see accessory 111.847.00.1)
- Flush valve features settings to enable either a 6 l and 3 l flush or a 4.5 l and 3 l flush. Note: must be used with pans designed for low volume flush.
- The cistern can be operated with used water (rainwater) provided it is passed through a filter system first.

**Technical data**

|                                  |             |
|----------------------------------|-------------|
| Flow pressure range              | 0.1-10 bar  |
| Operating temperature water max. | 25 °C       |
| Flush volume small range         | 2.6-4 l     |
| Flush volume factory setting     | 5.8 and 3 l |

## Scope of delivery

- 2 Duofix PreWall brackets for system
- Water supply connection R 1/2" male BSP parallel thread with integrated angle stop valve and hand wheel
- Conduit pipe for the water supply connection of Geberit AquaClean
- Flush bend
- Protection plug
- Protection housing for service opening
- 2 threaded rods M12 for ceramics fastening
- WC connection set,  $\varnothing$  90 mm
- WC outlet bend, HDPE,  $\varnothing$  90 mm
- Adaptor sleeve, HDPE,  $\varnothing$  90/110 mm
- Fastening material

Excluded:

- Flush plate

## Article

| Article no.  | PU1 | PU4 |
|--------------|-----|-----|
| 111.383.00.5 | 1   | 12  |