
TECHNICAL DATA SHEET

EMOTION ROUND CONCEALED THERMOSTATIC BATH/SHOWER MIXER (3 OUTLET)

TBTS-06-2344 **Product Code** Construction Brass Body (CuZn38b18) Chrome plated to BS EN 248 Finishes **Product Type** Contemporary Water Pressure Min.0.5 bar, Max. 7.0 bar Suitable for all plumbing systems, preferably balanced. Min. supply pressure **Plumbing Systems** differential requirement is 5:1 Complies with BSEN 1111 Standards Manufactured to comply with TMV2 Certification Thermostatic Cartridge Inlet: 3/4" Female Fitting Outlet: One 1/2" Female and two 3/4" Female Packaging 42x28.5x32cm / carton (4pcs/carton) Guarantee 15 years (3 years on working parts/decorative finish) **Additional Information** 1. Temperature: Pre-set 38°C, with push button override to 48°C. 2. Automatic shut off in the event of hot or cold water supply failure. 3. Easy accessible check valve





Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
		7.5		10.7	15.0	18.5	21.5	27.0	-	-

62.5

80

80

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.